

# SheerWeave® Style 4550/4650

## Specifications

■ Using thin polyester yarns and a unique twill weave, Styles 4550 and 4650 are easy to fabricate and offer a distinct two-sided appearance that maximizes both visibility and solar heat reduction. Style 4550/4650 can also be used in exterior roller shades.

**Fire Classification:** California U.S. Title 19 (small scale), ASTM E 84 (Class 1), BS 5867 2008 Part 2 Type B Performance, NFPA 701 TM#1 Small Scale and CAN/ULC-S109-03 (large and small scale)

**Bacteria and Fungal Resistance:** ASTM E 2180, ASTM G22, AATCC30 Part 3, ASTM D 3273, GREENGUARD Mold and Bacteria Standard ASTM 6329; includes Microban antimicrobial additives

**Environmental Certification:** GREENGUARD Certified and GREENGUARD for Children and Schools Certified

**Lead Free:** RoHS / Directive 2002/95/EC, US Consumer Product Safety Commission Section 101, ANSI/WCMA A100.1-2007 for lead content and REACH (EC 1907/2006) compliant

**Standard Uses:** Roll-up shades, Roman shades, folding shades, pleated shades, vertical blinds, panel tracks, sheers and screens

**Warranty:** 10-year interior; 5-year exterior



## Style 4550

**Standard Widths:** 63" and 98" (160.0cm and 248.9cm)

**Standard Roll Length:** 30 Linear Yards (27.4m)

**Composition:** 17% Polyester, 83% Vinyl on Polyester

**Mesh Weight:** 12.5 oz/yd<sup>2</sup> (423.83 g/m<sup>2</sup>)

**Fabric Thickness:** .025 in (0.64mm)

**Openness Factor:** Approximately 5%

**UV Blockage:** Approximately 95%

Solar Heat Control Properties of  
Phifer SheerWeave Style 4550  
Fabrics Installed Internally, Zero-Degree Profile Angle

Style No.	Color	*Solar Optical Properties				Shading Coefficient w/				
		TS	RS	AS	TV	Single			-Insulating-	
		1/8CL	1/4CL	1/4HA	1CL	1HA				
P10	Granite	7	56	37	8	0.38	0.38	0.34	0.36	0.28
P65	Linen	9	59	32	10	0.36	0.36	0.33	0.34	0.27
V45	Coal	8	48	44	9	0.44	0.43	0.37	0.40	0.30
V47	Chestnut	9	48	43	11	0.44	0.43	0.37	0.40	0.30

## Style 4650

**Standard Widths:** 63" and 98" (160.0cm and 248.9cm)

**Standard Roll Length:** 30 Linear Yards (27.4m)

**Composition:** 17% Polyester, 83% Vinyl on Polyester

**Mesh Weight:** 13.3 oz/yd<sup>2</sup> (450.96 g/m<sup>2</sup>)

**Fabric Thickness:** .026 in (0.66mm)

**Openness Factor:** Approximately 3%

**UV Blockage:** Approximately 97%

Solar Heat Control Properties of  
Phifer SheerWeave Style 4650  
Fabrics Installed Internally, Zero-Degree Profile Angle

Style No.	Color	*Solar Optical Properties				Shading Coefficient w/				
		TS	RS	AS	TV	Single			-Insulating-	
		1/8CL	1/4CL	1/4HA	1CL	1HA				
P10	Granite	6	55	39	8	0.39	0.38	0.34	0.36	0.28
P65	Linen	7	58	35	8	0.37	0.37	0.33	0.35	0.27
V45	Coal	5	47	48	7	0.44	0.43	0.37	0.40	0.30
V47	Chestnut	7	48	45	8	0.44	0.43	0.37	0.40	0.30

\* Performance evaluations conducted by Matrix, Inc., Mesa, Arizona.

TS = Solar Transmittance      1/8 CL = 1/8" Clear Glass  
RS = Solar Reflectance      1/4 CL = 1/4" Clear Glass  
AS = Solar Absorption      1/4HA = 1/4" Heat Absorbing Glass  
TV = Visual Transmittance

The solar optical properties are used to calculate the shading coefficient. The shading coefficient represents the percentage of solar heat gain that is transmitted to the interior through the glass and shading system. Darker colors provide maximum glare reduction and visibility. For complete technical information, current test results, performance specifications and larger samples, contact our Sun Control Marketing Department.



P. O. BOX 1700 • TUSCALOOSA, ALABAMA 35403-1700 U.S.A.  
PHONE: 205/345-2120 • TOLL FREE 1/800-221-5497  
FAX: 205/391-0799 • www.phifer.com